

You are here: [Home](#) > [Products](#) > [Uninterruptible Power Supply \(UPS\)](#) > [Smart-UPS On-Line](#)



APC Smart-UPS RT 20kVA 230V No Batteries , India Specific

Part Number: SURT20KUXI-IN



[Technical Specifications](#) [Product Overview](#) [Documentation](#) [Options](#)

Output

Output Power Capacity	16 kW / 20 kVA
Max Configurable Power	16 kW / 20 kVA
Nominal Output Voltage	230V
Output Voltage Note	Configurable for 400 or 415V 3 Phase nominal output voltage
Efficiency at Full Load	94.0%
Output Voltage Distortion	Less than 3%
Output Frequency (sync to mains)	50/60 Hz +/- 3 Hz user adjustable +/- 0.1
Other Output Voltages	220, 240, 400, 415
Crest Factor	3 : 1
Topology	Double Conversion Online
Output Connections	(1) Hard Wire 3-wire (H N + G) (4) IEC 320 C13 (4) IEC 320 C19 (4) IEC Jumpers



Bypass	Built-in Static Bypass, Internal Bypass (Automatic and Manual)	
Input		
Nominal Input Voltage	230V	
Input Frequency	40 - 70 Hz (auto sensing)	
Input Connections	Hard Wire 3-wire (3PH + G) Hard Wire 5-wire (3PH + N + G)	
Input voltage range for main operations	160 - 280V	
Other Input Voltages	220, 240, 400, 415	
Maximum Input Current	115A	
Input Breaker Capacity	125 A	
Batteries & Runtime		
Battery Type	No internal battery - uses external battery system	32 battery /384VDC
Communications & Management		
Interface Port(s)	DB-9 RS-232, RJ-45 10/100/1000 Base-T, Smart-Slot	
Pre-Installed SmartSlot™ Cards	AP9631	
Control panel	Multi-function LCD status and control console	
Audible Alarm	Audible and visible alarms prioritized by severity	
Emergency Power Off (EPO)	Yes	
Physical		
Maximum Height	263.00 mm	
Maximum Width	432.00 mm	
Maximum Depth	773.00 mm	
Rack Height	6U	
Net Weight	68.00 KG	
Shipping Weight	90.50 KG	
Shipping Height	622.00 mm	
Shipping Width	610.00 mm	
Shipping Depth	1003.00 mm	
Environmental		
Operating Environment	0 - 40 °C	
Operating Relative Humidity	0 - 95% no%	

Operating Elevation	0-3000 meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95% no%
Storage Elevation	0-15000 meters
Audible noise at 1 meter from surface of unit	59.00 dBA
Online Thermal Dissipation	2216.00 BTU/hr
Protection Class	IP 20

Conformance

Standard Warranty	2 years repair or replace
-------------------	---------------------------

Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains No SVHCs