

LUMINOUS

Jis Pe Desh Kare Bharosa



For Home UPS &
Inverter Battery Category

HIGH PERFORMANCE SOLAR BATTERIES



LUMINOUS SOLAR BATTERIES

Founded in 1988, Luminous Power Technologies (P) Limited today is a leading company with a differentiated portfolio of solutions for packaged power, diversified generation, electrical control & safety and energy optimisation.

With over 5000+ employees, 7 manufacturing units, 28 sales offices and more than 50000 channel partners; Luminous apart from its dominating position in the domestic market also has a strong foothold worldwide. Awarded with the 'Global Superbrands' status for the year 2011-12, ISO 50001:2011 certification and MNRE:CRISIL recognition, Luminous is passionately committed to bring uninterruptible and alternate power solutions to the customers that makes their life comfortable and efficient.

Solar Batteries

Luminous Solar Flooded Tubular Monoblock Batteries are designed to offer reliable, consistent and low maintenance power for renewable energy requirements and can be subject to deep cycle applications and minimum maintenance in rural and power deficit areas. The batteries have a capacity to withstand partial state of charge (PSOC) operation. These batteries are available in 12 Volts from 20Ah to 200 Ah @ C10 at 27°C.

Container and Lids	Polypropylene Co Polymer
Separators	Polyethylene envelope type
Positive Plate	Tubular low antimony
Negative Plate	Flat pasted
Connectors	Through partition welding
Vent Plugs	PP with float
Sulphuric Acid	1.240 0.010 sp. gravity when fully charged
Self discharge when charged	3% per month @ 27°C
Life Cycle	1500 cycles @ 80% DoD; 3000 cycles @ 50% DoD; 5000 cycles @ 20% DoD
Ah efficiency	Above 90%
Wh efficiency	Above 80%
Topping up frequency	Once in 8-10 months



SOLAR BATTERY APPLICATIONS

- Solar home lights
- Solar street lighting system
- Solar inverter
- Telecom towers
- Rural & urban electrification
- Power backup in small industry
- Solar power projects
- Various types of solar product



Technical Specifications

Model Name	Nominal Voltage	C10 Capacity upto 10.5V @ 27°C		Length ± 3 mm	Width ± 3 mm	Total Height (including terminal) ± 3 mm	Dry Weight ± 3% Kg	Filled Weight ± 3% Kg	Electrolyte Volume Litre
	V	Ah	KWH						
For Solar Models:									
LPT1220L	12	20	0.24	260.00	173.00	225.00	9.5	14.2	3.8
LPT1220H	12	20	0.24	260.00	173.00	225.00	10.50	17.5	5.6
LPT1240L	12	40	0.48	410.00	176.00	233.00	15.1	23.3	6.6
LPT1240H	12	40	0.48	410.00	176.00	233.00	15.6	24.8	7.4
LPT1275L	12	75	0.9	505.00	220.00	292.00	18.1	36.3	14.7
LPT1275H	12	75	0.9	505.00	220.00	258.00	20.6	38.1	14.1
LPT12100L	12	100	1.2	505.00	220.00	292.00	26.8	45.8	15.3
LPT12100H	12	100	1.2	517.00	272.00	250.00	27.1	47.5	16.5
LPT12135H	12	135	1.62	517.00	272.00	250.00	32.5	49.1	13.4
LPT12150TT	12	150	1.8	503.00	189.00	411.00	37.0	61.0	21.0
LPT12200L	12	200	2.40	503.00	189.00	411.00	41.5	65.5	19.0

Technical Specifications are subject to change without prior notice

LUMINOUS POWER TECHNOLOGIES PVT. LTD.

CB & C9, Community Centre, Janak Puri, New Delhi - 10058 (INDIA).

Phone: +91-11-40778221/222, Fax: +91-11-25558912, E-mail: mktg@luminousindia.com, Website: www.luminousindia.com