



Power in safe mode now

Presenting Line Interactive & Online UPS with power back up for your computers



PRO 600 Uno 600 Uno 800 Uno 1000



LD1000/2000/3000



| Specification | | | | | |
|------------------------------|------------------------------------|---------------|---------------|------------------------------------|---------------|
| Model | LB600UNO | | LB600PRO | LB800UNO | LB1000UNO |
| Capacity | 600VA / 360W | | 600VA / 360W | 800VA / 480W | 1000VA / 600W |
| INPUT | | | | | |
| Voltage | 230V | | | 230V | |
| Voltage Range | 140~300 VAC | | | 140~300 VAC | |
| Frequency Range | 50/60Hz (Auto sensing) | | | 50/60Hz (Auto sensing) | |
| OUTPUT | | | | | |
| Voltage Regulation | ±10% | | | ±10% | |
| Frequency Range (Batt. Mode) | 50/60Hz ± 1Hz | | | 50/60Hz ± 1Hz | |
| Transfer Time | Typical 4-8 ms, 13 ms max | | | Typical 4-8 ms, 13 ms max | |
| Waveform | Simulated Sine Wave | | | Simulated Sine Wave | |
| BATTERY | | | | | |
| Type & Number | 12V/7.2AH x 1 | 12V/7.5AH x 1 | 12V/7.2AH x 2 | 12V/7.2AH x 2 | |
| Charging Time | 6 hours up to 90% capacity | | | 4 - 6 hours up to 90% capacity | |
| DISPLAY | | | | | |
| AC Mode | Solid Green LED | | | Solid Green LED | |
| Battery Mode | Flashing Yellow LED | | | Flashing Yellow LED | |
| Fault Mode | Solid Red LED | | | Solid Red LED | |
| DISPLAY | | | | | |
| Dimensions (DxWxH) mm | 279 x 101 x 142 | | | 350 x 146 x 160 | |
| Net Weight (Kgs) | 4.2 | 4.4 | 7.9 | 7.9 | |
| ENVIRONMENT | | | | | |
| Humidity | 0-90 % RH@ 0-40°C (non-condensing) | | | 0-90 % RH@ 0-40°C (non-condensing) | |
| Noise Level | Less than 40 dB | | | Less than 40 dB | |